

PRODUKTDATENBLATT RTC

DALI PRO CONT-4 RTC | Steuergeräte



Anwendungsgebiete

- Room control, floor control, daylight-dependent control
- Connection of light and presence sensors in DALI systems
- Conference rooms
- Offices: Individual and group workplaces
- Production and assembly facilities
- Suitable for indoor applications
- Large luminaire groups
- Industry
- Corridors
- Strip lighting
- Logistic centers
- Classrooms
- Sports halls
- Training rooms

Produktvorteile

- Easy and intuitive control via App
- Control up to 1024 DALI ECGs via LAN interconnectivity
- Plug and Play preconfigured for instant use without any startup procedure
- Mains voltage interruption buffer battery
- All the luminaires in the system can be dimmed or switched
- Simple creation of scenes and sequences
- Switching and dimming of up to 256 DALI ECGs per DALI Professional control unit
- A setpoint for daylight-dependent control can be stored by double clicking
- Sensor integration in DALI
- Remote access/remote maintenance

Produkteigenschaften

- Interconnection of up to 4 DALI Professional control units
- Configuration via LAN/WLAN/USB
- RGB color sequences
- Time-of-day-dependent color temperature adjustment (human centric lighting)

- Controller for 4 DALI lines
- Up to 50 pushbutton/sensor couplers can be integrated
- Integrated DALI supply
- 4 freely programmable switchover relays; load contact: 4x 5 A
- Daylight-dependent and/or presence-dependent or manual control
- Up to 4 x 16 groups can be controlled
- Integrated clock for event control
- Weekly scheduler
- Connection via push-in terminals
- Control of lighting scenes and sequences (recall/store)
- Housing for series installation
- Length of the DALI control cable: up to 300 m

TECHNISCHE DATEN

Elektrische Daten

Nennleistung	20,00 W
Nennspannung	100...240 V

Maße & Gewicht

Länge	90.00 mm
Breite	160.00 mm
Breite (einschließlich runde Leuchten)	160.00 mm
Höhe	62.00 mm
Länge (einschließlich runde Leuchten)	62.00 mm
Produktgewicht	400,00 g

Temperaturen & Betriebsbedingungen

Umgebungstemperaturbereich	0...+40 °C
----------------------------	------------

Einsatzmöglichkeiten

Dimmbar	Nein
DIM-Schnittstelle	DALI
Anzahl der Steuerausgänge	4

Zertifikate & Standards

Schutzklasse	I
Schutzart	IP20



Daten gemäß der Verordnung zur Energieverbrauchskennzeichnung EU 2019/2015

Ähnliche Farbtemperatur	RANGE
-------------------------	-------

TECHNISCHE AUSSTATTUNG

- Free smartphone App for iOS and Android
- Suitable for up to 256 electronic control gears with DALI interfaces
- Graphic configuration software with Windows user interface

DOWNLOADS

DOWNLOADS	
	User instruction 334212_Technical instructions
	User instruction 545963_Software Manual DALI Pro 1.6.0 (GB)

DOWNLOADS



User instruction
339321_Software Bedienungsanleitung DALI Pro RTC (G)



User instruction
341214_DALI PRO CONT-4 RTC battery elimination



Certificates
EAEC N RU D-DE.MYu62.B.02241 20 17.09.2020-16.09.2025



Declarations of conformity
334811_Declaration of conformity – DALI PRO CONT-4 – DALI PRO PB Coupler – DALI PRO Sen



Advertisements
350862_7KZW003 Profispot 2-13 Beileger LMS (GB)

VERPACKUNGSMFORMATIONEN

EAN	Verpackungseinheit (Stück pro Einheit)	Abmessungen (Länge x Breite x Höhe)	Bruttogewicht	Volumen
4008321710871	Faltschachtel 1	215 mm x 95 mm x 76 mm	440.00 g	1.55 dm ³
4008321710888	Versandschachtel 10	490 mm x 229 mm x 172 mm	4645.00 g	19.30 dm ³

Die genannten Produktnummern beschreiben die kleinste bestellbare Mengeneinheit. Eine Versandeinheit kann mehrere Einzelprodukte beinhalten. Als Bestellmenge verwenden Sie bitte das Ein- oder Mehrfache einer Versandeinheit.

Referenzen / Verweise

– Konfigurationssoftware unter www.ledvance.de/software

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.