

PRODUKTDATENBLATT LF1200 -G3-830-09 discontinued

LINEARlight FLEX® POWER 1200 | LED-Module für professionelle und industrielle Anwendungen



Anwendungsgebiete

- Architecture lighting
- Cove lighting
- Ceiling integration
- Wall integration

Produktvorteile

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Large selection of light colors
- Great design freedom thanks to flexibility and cuttability of module
- Simple mounting and connection
- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- "Shop White" versions available for great color rendering without yellowing effect
- Extraordinary design and high quality materials
- Type of protection: IP00

Produkteigenschaften

- Flexible and cuttable LED strip



- Luminous flux: up to 1,200 lm/m
- Module efficacy: up to 152 lm/W
- Dimmable with PWM technology

TECHNISCHE DATEN

Elektrische Daten

| | |
|--------------------------|---------------------|
| Nennleistung | 80,10 W |
| Bemessungsleistung | 80.10 W |
| Nennleistung pro Meter | 8,9 W |
| Nennspannung | 24 V |
| Eingangsspannungsbereich | 23...25 V |
| Sperrspannung | 25 V |
| Stromart | Gleichspannung (DC) |
| Nennstrom | 3200 mA |

Photometrische Daten

| | |
|--|----------|
| Nutzbarer Gesamtlichtstrom | 10800 lm |
| Lichtausbeute | 135 lm/W |
| Lichtstrom | 10800 lm |
| Lichtstrom pro Meter | 1200 lm |
| Farbtemperatur | 3000 K |
| Farbwiedergabeindex Ra | 80 |
| Lichtfarbe LED | Weiß |
| Lichtfarbe (Bezeichnung) | 3000 K |
| Standardabweichung des Farbgleichs | ≤3 sdcn |
| Lichtstromerhalt am Ende der Nennlebensdauer | 0.70 |


Lichttechnische Daten

| | |
|---------------------------|----------|
| Ausstrahlungswinkel | 120 ° |
| Bemessungshalbwertswinkel | 120.00 ° |
| Startzeit | < 0.5 s |
| Aufwärmzeit (60 %) | 0.00 s |

LED MODULE INFORMATION

| | |
|--------------------------------|-----|
| Anzahl LEDs pro Meter | 70 |
| Anzahl LED je Modul | 630 |
| Anzahl LED je kleinste Einheit | 7 |

Maße & Gewicht



| | |
|--|----------|
| Länge | 9000 mm |
| Länge - kleinste Einheit | 100.0 mm |
| Breite | 8.00 mm |
| Breite (einschließlich runde Leuchten) | 8.00 mm |
| Höhe | 1.40 mm |
| Länge (einschließlich runde Leuchten) | 1.40 mm |
| LED-Abstand | 14,3 mm |
| Produktgewicht | 116,00 g |

Temperaturen & Betriebsbedingungen

| | |
|-------------------------------------|---------------------------|
| Umgebungstemperaturbereich | -20...+50 °C |
| Maximale Temperatur am Messpunkt tc | 75 °C |
| Betriebstemperaturbereich | -20...90 °C ¹⁾ |
| Betriebstemperatur nach IEC 62717 | 40 °C ²⁾ |

1) Das Überschreiten der Maximalwerte verringert die erwartete Lebensdauer oder zerstört das LED-Band.

2) Tp rated. Tp point coincides with Tc point - marked on device

Lebensdauer

| | |
|-------------------------|---------|
| Anzahl der Schaltzyklen | ≥ 15000 |
|-------------------------|---------|

Zusätzliche Produktdaten

| | |
|-----------------------|---|
| Anmerkung zum Produkt | <p>Perfekt auf OSRAM OPTOTRONIC® LED-Treiber abgestimmte Module (siehe entsprechende Tabelle) / Aktuelle lichttechnische Daten und wichtige Sicherheits-, Installations- und Anwendungsinformationen finden Sie unter http://www.osram.com/led-systems. / Alle technischen Parameter gelten für das ganze Modul. Aufgrund des komplexen Herstellungsprozesses von Leuchtdioden stellen die angegebenen typischen Werte der technischen LED-Parameter nur rein statistische Größen dar, die nicht notwendigerweise den tatsächlichen technischen Parametern jedes einzelnen Produkts, das vom typischen Wert abweichen kann, entsprechen.</p> |
|-----------------------|---|

Einsatzmöglichkeiten

| | |
|-------------------|-------|
| Dimmbar | Ja |
| DIM-Schnittstelle | PWM |
| Montageart | Anbau |



| | |
|-----------------------|-------|
| Kleinster Biegeradius | 20 mm |
| Selbstklebend | Ja |

Zertifikate & Standards

| | |
|------------------------|---|
| Normen | CE; ENEC 10 VDE / EAC / UL anerkannte Komponente gem. UL 8750 |
| Schutzart | IP00 |
| Energieverbrauch | 88.00 kWh/1000h |
| Energieeffizienzklasse | A++ |

LOGISTISCHE DATEN

| | |
|------------------------|-------------|
| Lagertemperaturbereich | -40...80 °C |
|------------------------|-------------|

Daten gemäß der Verordnung zur Energieverbrauchskennzeichnung EU 2019/2015

| | |
|-------------------------|--------------|
| Ähnliche Farbtemperatur | SINGLE_VALUE |
|-------------------------|--------------|

TECHNISCHE AUSSTATTUNG












- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V electronic control gears

ZUSÄTZLICHE PRODUKTINFORMATIONEN

- Some LED modules are equipped with a self-adhesive tape for attaching the LED module to suitable materials, such as aluminum profiles, which must be clean and free of oil or silicone coatings, as well as other dirt/dust particles. The adhesive tape is intended for single use and if removed may damage the material to which it is stuck and the LED module itself, which must then be scrapped. Use the adhesive tape when the installation material temperature is in the 18 °C...35 °C range. Complete adhesion takes up to 72 h.
- LED modules are designed for static installations in accordance with IPC 6013C – Use A. Take material vibrations, repetitive torsion, and elongation/compression into account.
- If the operating environment covers a broad temperature range (e.g. outdoor applications) and the operating length is longer than 2 m, the use of adequate mounting surfaces is required. The use of an additional thicker adhesive tape between LED module and mounting surface is also recommended in order to absorb the stress of any mismatch in expansion. Assure enough space for module expansion with increasing temperature.
- The manufacturer is not responsible for damage due to chemical corrosion. The user must provide suitable protection against corrosive agents such as moisture and condensation and any other harmful elements/compounds. Make certain to avoid corrosive atmospheres. According to the current state of LED technology, hydrogen sulfide (H2S) causes accelerated corrosion which leads to shortened lifetime or premature failure. Sources of H2S may be rubber, foam rubber, soft-foam tapes, rubber-based sealing, natural sources (e.g. sulfur springs), etc. To avoid H2S from sulfur-vulcanized rubber use silicon-based materials or peroxide-crosslinked rubber instead. Follow the recommendations in the material datasheet of the rubber supplier.
- IP00 LED modules, as manufactured, have no conformal coating and therefore offer no inherent protection against corrosion. Conformal coating treatment is possible, however materials must be selected properly in order to avoid product damage or impaired performance; the user must also completely seal the cut parts (ends/edges).
- For applications involving exposure to humidity and dust the module must be protected by a fixture or housing with a suitable IP protection class.
- Consult OSRAM Technical Service for further advice.
- Only a qualified electrician may install the module.
- Handle with care and ensure that there is no mechanical product damage, including damage to invisible internal electronics parts.
- Exceeding maximum operating and storage temperature ratings can reduce the expected lifetime or even destroy the LED module. The temperature of the LED module must be measured at the Tc-point in accordance with EN 60598-1 under steady-state conditions, considering the

- worst case; drive all channels at 100 % power. Refer to the product drawing for the exact location of the Tc-point.
- Exceeding the maximum ratings for the operating voltage causes hazardous overload and will likely destroy the LED module.
- Installation of LED modules and connection to the power supply must comply with all applicable electrical and safety standards.
- Observe correct polarity and wiring diagrams! Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Never exceed the maximum operable length, including daisy-chaining connections.
- Always ensure electrical isolation between the LED module and the mounting surface, especially in the vicinity of connections or cut ends.
- IP00 LED modules are ESD-sensitive; take adequate precautions during installation and operation of the products.
- Use only SELV LED drivers in accordance with applicable lighting standards and LED module ratings. In order to safely operate OSRAM LED modules it is necessary to supply them with an electronically stabilized power supply providing protection against short circuits, overload and overheating. To simplify the approval process of the luminaire/installation, the electronic power supplies control gear for LED modules must bear the CE and ENEC marking. In Europe the Declarations of Conformity must include at least the following standards: EN 61347-2-13, EN 55015, EN 61547 and EN 61000-3-2. ENEC certification will be based on EN 61347-2-13 and EN 62384. OSRAM OPTOTRONIC LED drivers comply with all relevant standards and guarantee safe operation; see the relevant brochure for more detailed information about OSRAM OPTOTRONIC.
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

DOWNLOADS

| DOWNLOADS | |
|--|--|
|  | User instruction LINEARlight FLEX POWER |
|  | PRODUKTDATENBLATT LINEARlight FLEX POWER Specification Sheet (EN) |
|  | Certificates EAC Certificate |
|  | Certificates VDE_ENEC+ Certificate |
|  | Certificates ENEC10_VDE Certificate |
|  | Certificates UL Certificate |
|  | Certificates CB TEST CERTIFICATE DE1-57844 |
|  | Declarations of conformity Manufacturer declaration |
|  | Declarations of conformity Declaration of conformity LINEARlight FLEX |
|  | Declarations of conformity EU Declaration of conformity |
|  | Declarations of conformity LF HP G3 CE 3420012 03 071119 |



DOWNLOADS



Declarations of conformity
LF HP G3 CE 4160937 00 071119



IES file (IES)
727123_LF1200-G3-830-09_IES



LDT file (Eulumdat)
727124_LF1200-G3-830-09_ldt



Advertisements
Light is freedom of design (EN)



Advertisements
Light is freedom of design (DE)

VERPACKUNGSMFORMATIONEN

| EAN | Verpackungseinheit (Stück pro Einheit) | Abmessungen (Länge x Breite x Höhe) | Bruttogewicht | Volumen |
|---------------|--|-------------------------------------|---------------|----------------------|
| 4052899953086 | Faltschachtel 1 | 29 mm x 190 mm x 186 mm | 208.00 g | 1.02 dm ³ |
| 4052899954274 | Versandschachtel 8 | 241 mm x 195 mm x 205 mm | 1861.00 g | 9.63 dm ³ |

Die genannten Produktnummern beschreiben die kleinste bestellbare Mengeneinheit. Eine Versandeinheit kann mehrere Einzelprodukte beinhalten. Als Bestellmenge verwenden Sie bitte das Ein- oder Mehrfache einer Versandeinheit.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.